

APPENDIX A

Network-Level Procedures

The notation $LSU(update_list)$ represents a link-state-update message that includes the updates (u, v, c, sn) in the $update_list$.

```

5      Process_Update(i, nbr, in_message){
        // Called when an update message in_message is received from nbr.
        Update_Topology_Table(i, nbr, in_message, update_list).
        Update_Parents(i).
        For each node src in TT_i {
10         Let update_list(src) consist of all tuples (k, l, c, sn) in update_list such that
            k = src.
            If update_list(src) is nonempty
                Send message LSU(update_list(src)) to children_i(src).}}

        Update_Topology_Table(i, nbr, in_message, update_list){
15         Set update_list to empty list.
        For each ((u,v,c,sn) in in_message) {
            If (p_i(u) == nbr) {
                If ((u,v) is in TT_i and sn > TT_i(u,v).sn) {
20                 Add (u,v,c,sn) to update_list.
                 Set TT_i(u,v).sn = sn.
                 Set TT_i(u,v).c = c.
                 If (sn > sn_i(u)) Set sn_i(u) = sn.}
                If ((u,v) is not in TT_i) {
25                 Add (u,v,c,sn) to TT_i.
                 Add (u,v,c,sn) to update_list.
                 If (sn > sn_i(u)) Set sn_i(u) = sn.}}}}

        Link_Change(i,j){
            // Called when the cost of link (i,j) changes.
            If (|TT_i(i,j).c - cost(i,j)|/TT_i(i,j).c > epsilon) {
30             Set TT_i(i,j).c = cost(i,j).
             Set TT_i(i,j).sn = current time stamp SN_i.
             Set update_list = {(i, j, TT_i(i, j).c, TT_i(i, j).sn)}
             Send message LSU(update_list) to children_i(i).}}

        Link_Down(i,j){
35         // Called when link (i,j) goes down.
        Remove j from N_i.
        Set TT_i(i,j).c = infinity.

```

00:02:02 02:08:26

```

Set TT_i(i,j).sn = current time stamp SN_i.
Update_Parents(i).
For each (node src in TT_i) remove j from children_i(src).
Set update_list = {(i,j, infinity, TT_i(i,j).sn)}.
5 Send message LSU(update_list) to children_i(i).}

Link_Up(i,j){
    // Called when link (i,j) comes up.
    Add j to N_i.
    Set TT_i(i,j).c = cost(i,j).
10 Set TT_i(i,j).sn = current time stamp SN_i.
    Update_Parents(i).
    Set update_list = {(i, j, TT_i(i,j).c, TT_i(i,j).sn)}.
    Send message LSU(update_list) to children_i(i).}

Update_Parents(i){
15 Compute_New_Parents(i)
    For each (node k in N_i){
        Set cancel_src_list(k), src_list(k), and sn_list(k) to empty.}
    For each (node src in TT_i such that src != i){
        If (new_p_i(src) != p_i(src)){
20 If (p_i(src) != NULL){
            Set k = p_i(src).
            Add src to cancel_src_list(k).}
        Set p_i(src) = new_p_i(src).
        If (new_p_i(src) != NULL){
25 Set k = new_p_i(src).
            Add src to src_list(k).
            Add sn_i(src) to sn_list(k).}}}
    For each (node k in N_i){
        If (src_list(k) is nonempty){
30 Send message NEW PARENT(src_list(k), sn_list(k)) to k.}
        If (cancel_src_list(k) is nonempty){
            Send message CANCEL PARENT(cancel_src_list(k)) to k.}}}

Compute_New_Parents(i){
    For each (node src in TT_i such that src != i){
35 Set new_p_i(src) = NULL.}
    Compute min-hop paths using Dijkstra.
    For each (node src in TT_i such that src != i){
        Set new_p_i(src) equal to the neighbor of node i along the minimum-hop
        path from i to src.}}

40 Process_New_Parent(i, nbr, src_list, sn_list){
    // Called when node i receives a NEW PARENT(src_list, sn_list) message from
    nbr.
    Set update_list to empty list.
```

09728020.120100
DOTDOT" 0208260

```

5      For each (node src in src_list) {
          Let sn_list.src denote the sequence number corresponding to src in sn_list.
          Add nbr to children_i(src).
          Set new_updates = {(k, l, c, sn) in TT_i such that k = src and sn >
10          sn_list.src}.
          Add new_updates to update_list.}
          Send message LSU(update_list) to nbr.}

10      Process_Cancel_Parent(i,nbr,src_list){
          // Called when node i receives a CANCEL PARENT(src_list) message from nbr.
          For each (node src in src_list) remove nbr from children_i(src).}

      Send_Periodic_Updates(i){
          Set update_list to empty.
          For each (j in N_i such that TT_i(i,j).c != infinity){
15          Set TT_i(i,j).sn = current time stamp SN_i.
          Add (i, j, TT_i(i,j).c, TT_i(i,j).sn) to update_list. }
          Send message LSU(update_list) to children_i(i).}

      Compute_New_Parents2(i){
          S ← ∅;
20          For each (v ∈ TT_i) {
              Set d(v) = infinity;
              Set pred(v) = NULL;
              Set new_p_i(v) = NULL; }
          d(i) ← 0;
25          While (there exists w ∈ TT_i – S such that d(w) < infinity){
              Set u = node w ∈ TT_i – S that minimizes d(w);
              Set S = S ∪ {u};
              For each (v such that (u, v) ∈ TT_i) {
                  If (d(u) + 1 < d(v) or [d(u) + 1 = d(v) and new_p_i(u) = p_i(v)]) {
30                  Set d(v) = d(u) + 1;
                  Set pred(v) = u;
                  If (u = i) Set new_p_i(v) = v;
                  Else Set new_p_i(v) = new_p_i(u); } } } }
```

Partial-Topology 1

35 The function Mark_Special_Links() is called whenever the parent p_i(src) or the set of children children_i(src) for any source src changes. The notation LSU(update_list) represents a link-state-update message that includes the updates (u, v, c, sn, sp) in the update_list, where sp is

a single bit that indicates whether the link is “special”, i.e., whether it should be broadcast to all nodes.

```

Mark_Special_Links(i){
    For all (outgoing links (i,j)) {Set TT_i(i,j).sp = 0;}
5    For all (nodes src != i){
        if (p_i(src) != NULL and p_i(src) != src){
            Set TT_i(i, p_i(src)).sp = 1;} //Link is special.
            For all (nodes j in children_i(src)){
                Set TT_i(i,j).sp = 1;} //Link is special.
10    }
}

Update_Topology_Table(i, nbr, in_message, update_list){
    Set update_list to empty list.
    For each ((u,v,c,sn,sp) in in_message) {
15        If (p_i(u) = nbr) {
            If ((u,v) is in TT_i and sn > TT_i(u,v).sn) {
                Set TT_i(u,v).sn = sn.
                Set TT_i(u,v).c = c.
                Set TT_i(u,v).sp = sp.
20                (Only links marked as special are forwarded.)
                If (sp = 1) Add (u,v,c,sn,sp) to update_list.
                If (sn > sn_i(u)) Set sn_i(u) = sn.}
            If ((u,v) is not in TT_i) {
                Add (u,v,c,sn,sp) to TT_i.
                If (sp = 1) Add (u,v,c,sn,sp) to update_list.
                If (sn > sn_i(u)) Set sn_i(u) = sn.}}}}
25

Process_Update(i, nbr, in_message){
    // Called when an update message in_message is received from nbr.
30    Update_Topology_Table(i, nbr, in_message, update_list).
    Update_Parents(i).
    Mark_Special_Links(i).
    For each node src in TT_i {
        Let update_list(src) consist of all tuples (k, l, c, sn, sp) in update_list such
35        that k = src.
        If update_list(src) is nonempty
            Send message LSU(update_list(src)) to children_i(src).}}

Link_Change(i,j){
    // Called when the cost of link (i,j) changes.
40    If (|TT_i(i,j).c - cost(i,j)|/TT_i(i,j).c > epsilon) {
        Set TT_i(i,j).c = cost(i,j).
        Set TT_i(i,j).sn = current time stamp SN_i.

```

Set update_list = {(i, j, TT_i(i, j).c, TT_i(i, j).sn, TT_i(i, j).sp)}.
 Send message LSU(update_list) to children_i(i).}}

Link_Down(i, j){
 // Called when link (i, j) goes down.
 5 Remove j from N_i.
 Set TT_i(i, j).c = infinity.
 Set TT_i(i, j).sn = current time stamp SN_i.
 Update_Parents(i).
 For each (node src in TT_i) remove j from children_i(src).
 10 Mark_Special_Links(i).
 Set update_list = {(i, j, infinity, TT_i(i, j).sn, TT_i(i, j).sp)}.
 Send message LSU(update_list) to children_i(i).}

Link_Up(i, j){
 // Called when link (i, j) comes up.
 15 Add j to N_i.
 Set TT_i(i, j).c = cost(i, j).
 Set TT_i(i, j).sn = current time stamp SN_i.
 Update_Parents(i).
 Mark_Special_Links(i).
 20 Set update_list = {(i, j, TT_i(i, j).c, TT_i(i, j).sn, TT_i(i, j).sp)}.
 Send message LSU(update_list) to children_i(i).}

Update_Parents(i){
 Compute_New_Parents(i).
 For each (node k in N_i)
 25 Set cancel_src_list(k), src_list(k), and sn_list(k) to empty.
 For each (node src in TT_i such that src != i){
 If (new_p_i(src) != p_i(src)){
 If (p_i(src) != NULL){
 30 Set k = p_i(src).
 Add src to cancel_src_list(k).}
 Set p_i(src) = new_p_i(src).
 If (new_p_i(src) != NULL){
 Set k = new_p_i(src).
 Add src to src_list(k).
 35 Add sn_i(src) to sn_list(k).}}}
 For each (node k in N_i){
 If (src_list(k) is nonempty){
 Send message NEW PARENT(src_list(k), sn_list(k)) to k.)
 If (cancel_src_list(k) is nonempty{
 40 Send message CANCEL PARENT(cancel_src_list(k)) to k.}}}

Compute_New_Parents(i){
 For each (node src in TT_i such that src != i){
 Set new_p_i(src) = NULL.}


```

    for each (node  $k \in \text{children}_i(\text{src})$ ){
        Add  $\text{update\_list}(\text{src})$  to  $\text{out\_message}(k)$ ;
    }
    For each (node  $k \in N_i$  s.t.  $\text{out\_message}(k)$  is non-empty){
5      Send the message  $\text{out\_message}(k)$  to node  $k$ ;
    }

Update_Topology_Table( $i, k, \text{in\_message}$ ){
    For each  $((u, v, c) \in \text{in\_message})$ {
        // Process only updates received from the parent  $p_i(u)$ 
10      if ( $p_i(u) = k$  or  $k = i$ ){
            if  $((u, v) \notin \text{TT}_i$  or  $c \neq \text{TT}_i(u, v).c$ {
                 $\text{TT}_i(u, v) \leftarrow (u, v, c)$ ;
                Mark  $(u, v)$  as changed in  $\text{TT}_i$ ;
            }
        }
15      }
    if ( $\text{in\_message}$  is a PARENT_RESPONSE){
        For each ( $u$  such that  $\text{in\_message}$  includes source  $u$ ){
            if ( $p_i(u) = k$  and  $\text{pending}_i(u) = 1$ ){
                 $\text{pending}_i(u) = 0$ ;
20              For each ( $v$  such that  $\text{TT}_i$  contains an entry for  $(u, v)$ ){
                  if ( $\text{in\_message}$  does not contain update for link  $(u, v)$ ){
                       $\text{TT}_i(u, v).c \leftarrow \infty$ ;
                      // indicates link should be deleted
                      Mark  $(u, v)$  as changed in  $\text{TT}_i$ ;
25                  }
              }
            }
        }
30      }
    }

Process_Cancel_Parent( $i, \text{nbr}, \text{src\_list}$ ){
    For each ( $\text{src} \in \text{src\_list}$ )
35       $\text{children}_i(\text{src}) \leftarrow \text{children}_i(\text{src}) - \{\text{nbr}\}$ ;
    }

Generate_Updates( $i, \text{update\_list}$ ){
     $\text{update\_list} \leftarrow \emptyset$ ;
    for each (entry  $(u, v, c, c') \in \text{TT}_i$ ){
40      if  $((u, v)$  is in new  $T_i$  and  $((u, v)$  is marked as changed or is not in old  $T_i))$ {
            Add  $(u, v, c)$  to  $\text{update\_list}$ ;
             $T_i(u, v).c' \leftarrow T_i(u, v).c$ ;
             $R_i \leftarrow R_i \cup \{(u, v)\}$ ;
        }
    }
}

```

```

    }
    else if ((u, v) is in Ri but not in new Ti and  $c > c'$ ){
        Add (u, v,  $\infty$ ) to update_list; // delete update
         $Ti(u, v).c' \leftarrow \infty$ ;
5        Remove (u, v) from Ri;
    }
    if ( $TT\_i(u, v).c = \infty$ )
        Remove (u, v) from  $TT\_i$ ;
    }
10 }

Update_Parents(i){
    For each (node  $k \in N_i$ ){
        cancel_src_list( $k$ )  $\leftarrow \emptyset$ ;
        src_list( $k$ )  $\leftarrow \emptyset$ ;}
15    For each (node  $src \in TT\_i$  such that  $src \neq i$ ) {
        new_p_i( $src$ )  $\leftarrow$  next node on shortest path to  $src$ ;
        if (new_p_i( $src$ )  $\neq p\_i(src)$ ){
            if (new_p_i( $src$ )  $\neq \text{NULL}$ ) {
20                 $k \leftarrow p\_i(src)$ ;
                cancel_src_list( $k$ )  $\leftarrow$  cancel_src_list( $k$ )  $\cup \{src\}$ ;
            }
            if (new_p_i( $src$ )  $\neq \text{NULL}$ ){
                 $k \leftarrow new\_p\_i(src)$ ;
                src_list( $k$ )  $\leftarrow$  src_list( $k$ )  $\cup \{src\}$ ;
25            }
            p_i( $src$ )  $\leftarrow$  new_p_i( $src$ );
        }
    }
    For each (node  $k \in N_i$ ){
30        if (src_list( $k$ )  $\neq \emptyset$ )
            Send NEW_PARENT(src_list( $k$ )) to node  $k$ ;
        if(cancel_src_list( $k$ )  $\neq \emptyset$ )
            Send CANCEL_PARENT(cancel_src_list( $k$ )) to node  $k$ ;
    }
35 }

Process_New_Parent(i, nbr, src_list){
    update_list  $\leftarrow \emptyset$ ;
    for each (node  $u \in u\_list$ ) {
        children_i( $u$ )  $\leftarrow$  children_i( $u$ )  $\cup \{nbr\}$ ;
40        updates( $u$ )  $\leftarrow \{(u, v, c) \in TT\_i \text{ such that } (u, v) \in Ti\}$ ;
        update_list  $\leftarrow$  update_list  $\cup$  updates ( $u$ );
    }
    Send PARENT_RESPONSE(src_list, update_list) to  $nbr$ ;}

```